



ACETex® PET woven geotextiles are made of high strength polyester yarns to form a stable weaving structure. ACETex® PET Series provides a wide range of strength with high quality. ACETex® PET Series is suitable to stabilize the earth structure, such as MSE Wall or Steep Slope, Road, Bridge or Pavement Construction in long term or short term application.

Product Properties

Mechanical Index Properties	Test Method	Unit	GT100-I	GT200-I	GT300-I	GT400-I	GT600-I	GT800-I	GT1000-I	GT1200-I	GT100-II	GT200-II	GT300-II
-----------------------------	-------------	------	---------	---------	---------	---------	---------	---------	----------	----------	----------	----------	----------

Material High Tenacity Polyester Multifilament

Tensile Strength - MD	ASTM D4595	kN/m	100	200	300	400	600	800	1000	1200	100	200	300
Tensile Strength - CD	ASTM D4595	kN/m	50	50	50	50	50	50	100	100	100	200	300
Nominal Elongation - MD	ASTM D4595	%	10	10	10	10	10	10	10	10	12	12	12

Long Term Design Properties

Creep Strength at 120yrs	ASTM D5262 ASTM D6992	kN/m	66	133	200	266	400	533	666	800	66	133	200
Long Term Design Strength at 120yrs - Sandy gravel	FHWA NHI-10-024	kN/m	48	97	146	194	302	403	531	638	48	97	146

Dimensional Properties

Width		m	5	5	5	5	5	5	5	5	5	5	5
-------	--	---	---	---	---	---	---	---	---	---	---	---	---

Note.

1. Calculation of long term design strength is based on design code, FHWA NHI 00-043, which is determined by compounding three reduction factors for creep, installation damage, and environmental effects.

2. The maximum width of ACETex® PET woven geotextiles is up to 5.2m.

3. The values given are indicative and correspond to an average of results obtained in ACE laboratory and international testing institutions. The right is reserved to make changes without notice.

Disclaimer: This document is provided solely for general information, and shall not be construed as engineering advice, or part of the contract with any customer not withstanding anything to the contrary in the contract.

We hereby disclaim any liability in connection with any use of the information herein.

Thank you for your interests in our products,
We can customize the product to fulfill different project requirement. If you require more detail information,
please feel free to contact us directly at sales@geoace.com.

We'll be pleased to provide our best assistance.

Accurate, Collaborative, Efficient

TEL: 886-4-26595926 FAX: 886-4-26595935
E-mail: sales@geoace.com <http://www.geoace.com>